


Did You Know

about our...



HOBSON PRESS

Large Flange Rivet

TRUSS HEAD (DOME HEAD) – OPEN / LARGE FLANGE
SHELL - ALUMINIUM (ALLOY 5052) / STEM - CARBON STEEL ZP

Part	Size	Shell Diameter	Grip Range (mm)	Rec. Drilling Ø (mm)	Body Length (mm)	Clearance	Head Diameter (mm)	Pack
R9P73LAS402	#42	3.2	1.6-3.2	3.3	7.0	9.10	10	1000
R9P73LAS404	#44	3.2	4.8-6.4	3.3	10.2	12.20	10	1000
R9P73LAS406	#46	3.2	7.9-9.5	3.3	13.3	15.70	10	1000
R9P73LAS408	#48	3.2	9.5-12.7	3.3	16.5	19.10	10	1000
R9P73LAS504	#54	4.0	4.8-6.4	4.1	10.8	13.30	12	1000
R9P73LAS506	#56	4.0	6.4-9.5	4.1	14.0	16.50	12	1000
R9P73LAS603	#63	4.8	3.2-4.8	4.9	9.8	12.65	16	500
R9P73LAS604	#64	4.8	4.8-6.4	4.9	11.4	14.25	16	500
R9P73LAS606	#66	4.8	6.4-9.5	4.9	14.6	17.45	16	500
R9P73LAS610	#610	4.8	12.7-15.9	4.9	21.0	24.45	16	500
R9P73LAS612	#612	4.8	15.9-19.1	4.9	24.1	27.65	16	500
R9P73LAS614	#614	4.8	19.1-22.2	4.9	27.3	30.95	16	500
R9P73LAS616	#616	4.8	22.2-25.4	4.9	30.5	34.25	16	500



Head

Truss Head (Open) Dome	O	Protrudes above the face of the job, and used in most industrial applications.
Countersunk (Open)	O	No part of the fastener protrudes from the face of the material.
Large Flange Head	L	Large head diameter used for fastening soft materials.

Type

Open	O	The set rivet is not sealed by the stem.
Sealed	T	The mandrel is attached to the inside of the shell which ensures there are no gaps for water or air.
Multi-Grip	M	Provides a secure joint across various grip ranges.
Peel	P	Provide good cohesion of soft materials without distortion. Useful for uneven surfaces.
Grooved	G	Grooves around the shell mean effective holding power when set in less stiff materials e.g. Plastic
Triform (with washer)	W	During setting, the rivet body splits into 3 parts, preventing the material from being damaged.

1605031DYK

Quality Fasteners Since 1935



www.hobson.com.au