DID YOU KNOW?

about our...





Serrated Flanged Bolt and Nut D-LOK® Class 12.9

D-LOK® Flanged Serrated Class 12.9 - Bolt (Fully threaded).

The D-LOK® Bolt is designed for applications where there is constant vibration. It is fatigue resistant and re-usable with no decrease in performance.

Applications

- Equipment and machinery with constant vibration
- Forklift
- Trucks large vehicles
- Mining equipment
- · Motor bikes
- Conveyors materials handling equipment
- Defence and military vehicles


SERRATED FLANGED BOLT D-LOK® ZINC FLAKE SILVER / HEC / CLASS 12.9

Part	Size	Length	AF	Pack Qty
Prefix		(mm)	(mm)	
BF12FCM08	M8	16-35	13	100
BF12FCM10	M10	16-50	15	100
BF12FCM12	M12	25-30	17	100
BF12FCM12	M12	35-80	17	50
BF12FCM16	M16	30-90	22	25
BF12FCM20	M20	40-60	27	25
BF12FCM20	M20	70-90	27	20

SERRATED FLANGED NUT D-LOK®

ZINC FLAKE SILVER / HEC / CLASS 12

Part	Size	AF	Pack Qty
		(mm)	
NF12FCM08	M8	13	200
NF12FCM10	M10	15	200
NF12FCM12	M12	19	200
NF12FCM16	M16	24	200
NF12FCM20	M20	30	100



Features

- · Flanged no additional washer required.
- · Serrated to lock and clamp the connection.





Disclaimer: while every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees disclaim all liability in respect to anything or the consequences of anything done or omitted regarding the whole or any part of this document. HEC product marking is the manufacturing mark of Hobson Engineering. HEC is a registered trademark of Hobson Engineering.

Bolt Tension | Anti-Vibration | Product Reliability | Traceability

