DID YOU KNOW?

about our...





Lifting Eye Bolt and Nut

Bolt and nut are both approved and certified for lifting. Can be used in axial \updownarrow or angular \uparrow loading.

LIFTING EYE BOLT ZINC YELLOW PASSIVATE / DIN 580 / GRADE C15E

Part	QFind	Size	Height of eye	Length of thread	Pack Qty
			(mm)	(mm)	
ULEBC5YD5M06	EBCYM6	M6	36.0	13.0	100
ULEBC5YD5M08	EBCYM8	M8	36.0	13.0	100
ULEBC5YD5M10	EBCYM10	M10	45.0	17.0	50
ULEBC5YD5M12	EBCYM12	M12	53.0	20.5	50
ULEBC5YD5M16	EBCYM16	M16	62.0	27.0	25
ULEBC5YD5M20	EBCYM20	M20	71.0	30.0	10
ULEBC5YD5M24	EBCYM24	M24	90.0	36.0	5

LIFTING EYE NUT ZINC YELLOW PASSIVATE / DIN 582 / GRADE C15E

Part	QFind	Size	Height of eye	Collar thickness	Pack Qty
			(mm)	(mm)	
ULENC5YD5M06	ENCYM6	M6	36.0	8.5	100
ULENC5YD5M08	ENCYM8	M8	36.0	8.5	100
ULENC5YD5M10	ENCYM10	M10	45.0	10.0	50
ULENC5YD5M12	ENCYM12	M12	53.0	11.0	50
ULENC5YD5M16	ENCYM16	M16	62.0	13.0	25
ULENC5YD5M20	ENCYM20	M20	71.0	16.0	10
ULENC5YD5M24	ENCYM24	M24	90.0	20.0	5

FEATURES

- · Approved for lifting.
- Stamped with working load for axial loading.



You can download this Test Certificate and/or Report from our website:

hobson.com.au





MARKINGS:

- CE (European Conformity)
- · WLL (Working Load Limit)





MARKINGS:

- CE (European Conformity)
- WLL (Working Load Limit)

APPLICATIONS

- Connection point for: Anchoring, rigging, pulling, lifting or hoisting.
- Can be used with: rope, cables, shackles
 and books
- Threaded into steel: equipment, machine and structures.
- Bolted through steel or timber profiles and secured with a nut.

Disclaimer: While every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees, disclaim any and all liability to any person in respect of anything or the consequences of anything done or omitted to be done in reliance upon the whole or any part of this document.

HOBSON ENGINEERING