DID YOU KNOW?

about our...






Lifting Eye Bolt DIN 580

LIFTING EYE BOLT 316 STAINLESS / DIN 580 / GRADE A4

Part	QFind	Size	Dimensions (mm)			Working	Pack Qty
		M	Н	L	ØID	Load WLL (kg)	
ULEB16PD5M06	EB16M6	M6	36	13.0	20	75	50
ULEB16PD5M08	EB16M8	M8	36	13.0	20	140	50
ULEB16PD5M10	EB16M10	M10	45	17.0	25	230	25
ULEB16PD5M12	EB16M12	M12	53	20.5	30	340	10
ULEB16PD5M16	EB16M16	M16	62	27.0	35	700	10
ULEB16PD5M20	EB16M20	M20	71	30.0	40	1200	5
ULEB16PD5M24	EB16M24	M24	90	36.0	50	1800	2
ULFB16PD5M30	EB16M30	M30	109	45.0	60	3200	2

FEATURES

- Eye bolt approved and certified for lifting.
- Can be used in axial or angular loading.



3200 2

MARKINGS:





APPLICATIONS

- · Connection point for anchoring, rigging, pulling, lifting or hoisting.
- Can be used with ropes, cables, shackles and hooks.
- Threaded into steel equipment, machine and structures.
- Bolt through steel or timber profiles.

Disclaimer: While every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees, disclaim any and all liability to any person in respect of anything or the consequences of anything done or omitted to be done in reliance upon the whole or any part of this document.

