DID YOU KNOW?

about our...

MORE SIZES

AVAILABLE +





Socket Screw Countersunk Head

SOCKET SCREW COUNTERSUNK HEAD ZINC PLATED (ROHS COMPLIANT) / DIN 7991 / CLASS 010.9

Part	Size	Length	Pitch	Hex	Pack Qty
		(mm)	(mm)	(mm)	
SC10ZCM050010	M5	10	0.80	3	100
SC10ZCM050012	M5	12	0.80	3	100
SC10ZCM050016	M5	16	0.80	3	100
SC10ZCM050020	M5	20	0.80	3	100
SC10ZCM050025	M5	25	0.80	3	100
SC10ZCM050030	M5	30	0.80	3	100
SC10ZCM060035	M6	35	1.00	4	100
SC10ZCM060040	M6	40	1.00	4	100
SC10ZCM080050	M8	50	1.25	5	100
SC10ZCM100020	M10	20	1.50	6	100
SC10ZCM100045	M10	45	1.50	6	100
SC10ZCM100050	M10	50	1.50	6	100
SC10ZCM120025	M12	25	1.75	8	100
SC10ZCM120030	M12	30	1.75	8	100
SC10ZCM120035	M12	35	1.75	8	100
SC10ZCM160050	M16	50	2.00	10	25
SC10ZCM160065	M16	65	2.00	10	25



APPLICATIONS

Can be used in applications that do not require 012.9 strength as a cost effective option.

Marking symbols for fasteners with reduced loadability

marking symbols	TOT TUOTOTION	With Foundood .	loudubility
Property Class	8.8	10.9	12.9
Marking	08.8	010.9	012.9
010.9	0		



Disclaimer: While every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees, disclaim any and all liability to any person in respect of anything or the consequences of anything done or omitted to be done in reliance upon the whole or any part of this document.

