DID YOU KNOW?

about our...



Socket Screw Countersunk Head

SOCKET SCREW COUNTERSUNK HEAD PLAIN / DIN 7991 / CLASS 010.9

//	M
	-

I EAIN / BIN 1001/	OLAGO UIU.		
Part	Size	Length	Pack Qty
		(mm)	
SC10PCM050012	M5	12	100
SC10PCM050020	M5	20	100
SC10PCM050025	M5	25	100
SC10PCM080035	M8	35	100
SC10PCM080040	M8	40	100
SC10PCM080050	M8	50	100
SC10PCM080070	M8	70	100
SC10PCM100020	M10	20	100
SC10PCM100025	M10	25	100
SC10PCM100040	M10	40	100
SC10PCM100050	M10	50	100
SC10PCM120035	M12	35	100
SC10PCM120040	M12	40	100
SC10PCM120045	M12	45	100
SC10PCM120050	M12	50	50
SC10PCM160050	M16	50	25
SC10PCM160055	M16	55	25
SC10PCM160060	M16	60	25
SC10PCM160070	M16	70	25
SC10PCM160080	M16	80	25
SC10PCM160100	M16	100	25
SC10PCM160110	M16	110	25
SC10PCM200040	M20	40	25
SC10PCM200060	M20	60	25
SC10PCM200080	M20	80	25
SC10PCM200100	M20	100	25
SC10PCM200120	M20	120	10
SC10PCM200150	M20	150	10
SC10PCM200160	M20	160	10
SC10PCM240060	M24	60	10
SC10PCM240120	M24	120	5
NUEVA/			



APPLICATIONS

Can be used in applications that do not require 012.9 strength as a cost effective option.

Marking symbols for fasteners with reduced loadability 8.8 12.9 **Property Class** 10.9 8.80 010.9 012.9



Marking





Disclaimer: While every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees, disclaim any and all liability to any person in respect of anything or the consequences of anything done or omitted to be done in reliance upon the whole or any part of this document.

