

DID YOU KNOW?

about our...




**NEW
PRODUCT**

Hex Flange Nyloc® Nut (No Serration)

HEX FLANGE NYLOC® NUT (NO SERRATION) 304 STAINLESS / DIN 6926 / A2

304




Part	Size	AF	Pitch	Pack Qty
		(mm)	(mm)	
NF04PNNCM04	M4	7	0.70	100
NF04PNNCM05	M5	8	0.80	100
NF04PNNCM06	M6	10	1.00	100
NF04PNNCM08	M8	13	1.25	100
NF04PNNCM10	M10	15	1.50	100
NF04PNNCM12	M12	18	1.75	50
NF04PNNCM16	M16	24	2.00	50

FEATURE



Nyloc® nuts' usage of a thin ring of nylon inside the top of the nut prevents bolt loosening due to increased friction on the bolt thread.

The special nylon insert prevents loosening due to vibration.



NYLOC®

Nylon insert locknuts



Anti-vibration solution



You can download this Test Certificate and/or Report from our website:

hobson.com.au

Disclaimer: while every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees disclaim all liability in respect to anything or the consequences of anything done or omitted regarding the whole or any part of this document.

Bolt Tension | Anti-Vibration | Product Reliability | Traceability

hobson.com.au **QUALITY FASTENERS SINCE 1935**

