# **DID YOU KNOW?**

about our...





# **Grade 80 Eye Safety Hook**

Eye safety hook locks when a load is applied to prevent the release of chains and lifting slings.

## SAFETY HOOK WITH EYE POWDER COAT / HEC / GRADE 80

| Part         | Qfind | Size | WLL     | BL      | Pack Qty |
|--------------|-------|------|---------|---------|----------|
|              |       | (mm) | (tonne) | (tonne) |          |
| ULHK08PSE-06 | HSE6  | 6    | 1.12    | 4.48    | 10       |
| ULHK08PSE-08 | HSE8  | 8    | 2.00    | 8.00    | 10       |
| ULHK08PSE-10 | HSE10 | 10   | 3.15    | 12.60   | 5        |
| ULHK08PSE-13 | HSE13 | 13   | 5.30    | 21.20   | 5        |
| ULHK08PSE-16 | HSE16 | 16   | 8.00    | 32.00   | 2        |

#### **APPLICATIONS**

- · Use with Grade 80 lifting components
- · Lifting with chains and synthetic slings

## **FEATURES**

- Conf
- 100% magnaflux crack detection
- Safety hook prevents components from releasing if line becomes slack
- · Back lever releases hook





### **MARKINGS:**

- CE (European Conformity)
- WLL (Working Load Limit)
- Trace Code (linked to certificate online)
- Manufacturer's mark



Disclaimer: while every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees disclaim all liability in respect to anything or the consequences of anything done or omitted regarding the whole or any part of this document.

