

DID YOU KNOW?

about our...



**NEW
PRODUCT**

Grade 80 Clevis Safety Hook

Clevis safety hook locks when a load is applied to prevent the release of lifting slings.

CLEVIS SAFETY HOOK POWDER COAT / HEC / GRADE 80

Part	Qfind	Size	WLL	BL
		M	(tonne)	(tonne)
ULHK08PSC-06	HSC6	6	1.12	4.48
ULHK08PSC-08	HSC8	8	2.00	8.00
ULHK08PSC-10	HSC10	10	3.15	12.60
ULHK08PSC-13	HSC13	13	5.30	21.20
ULHK08PSC-16	HSC16	16	8.00	32.00
ULHK08PSC-20	HSC20	20	12.50	50.00

APPLICATIONS

- Use with Grade 80 lifting components
- Lifting with chains and synthetic slings
- Clevis fitting for direct connection to chain

FEATURES

- Conforms to AS 3776
- 100% magnaflux crack detection
- Safety hook prevents components from releasing when being lifted
- Back lever releases hook



MARKINGS:

- **CE** (European Conformity)
- **WLL** (Working Load Limit)
- **Trace Code** (linked to certificate online)
- **Manufacturer's mark**



You can download this
Test Certificate and/or
Report from our website:

hobson.com.au

Disclaimer: while every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees disclaim all liability in respect to anything or the consequences of anything done or omitted regarding the whole or any part of this document.

Bolt Tension | Anti-Vibration | Product Reliability | Traceability

hobson.com.au QUALITY FASTENERS SINCE 1935



230214DYK