## APPLICATIONS

- Use with Grade 80 lifting components
- · Lifting with chains and synthetic slings

#### FEATURES

- Conforms to AS 3776
- 100% magnaflux crack detection
- · Safety hook prevents components from releasing if line becomes slack

## **DID YOU KNOW?**

about our...

## **Grade 80 Clevis Sling Hook**

Self-locking clevis sling hook enables efficient and effective connection to lifting slings.

### CLEVIS SLING HOOK POWDER COAT / HEC / GRADE 80

Part	Qfind	Size	WLL	BL
		(M)	(tonne)	(tonne)
ULHK08PLC-06	HLC6	6	1.12	4.48
ULHK08PLC-08	HLC8	8	2.00	8.00
ULHK08PLC-10	HLC10	10	3.15	12.60
ULHK08PLC-13	HLC13	13	5.30	21.20
ULHK08PLC-16	HLC16	16	8.00	32.00
ULHK08PLC-20	HLC20	20	12.50	50.00

# 2.008.003.1512.605.3021.208.0032.002.5050.00



#### MARKINGS

- CE (European Conformity)
- WLL (Working Load Limit)
- Trace Code (linked to certificate online)
- Manufacturer's mark
- Size



Disclaimer: while every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees disclaim all liability in respect to anything or the consequences of anything done or omitted regarding the whole or any part of this document.



HOBSON

ENGINEERING

Bolt Tension | Anti-Vibration | Product Reliability | Traceability

hobson.com.au QUALITY FASTENERS SINCE 1935

