

DID YOU KNOW?

about our...



**NEW
PRODUCT**

ESL Dual Slot Self-Lock Nut

ESL DUAL SLOT SELF-LOCK NUT 304 STAINLESS / NFE 25 411 / A2-70 / LANFRANCO

Part	D	Pitch	H	M.	S	E
		(mm)	(mm)	(mm)	(mm)	(mm)
NJ04PESLM06	M6	1.00	7.00	3.60	10.00	11.05
NJ04PESLM08	M8	1.25	8.80	4.80	13.00	14.38
NJ04PESLM10	M10	1.50	11.00	6.00	16.00	17.77
NJ04PESLM12	M12	1.75	13.00	7.20	18.00	20.03
NJ04PESLM16	M16	2.00	18.70	11.50	24.00	26.75
NJ04PESLM20	M20	2.50	21.00	12.00	30.00	32.95
NJ04PESLM24	M24	3.00	25.50	15.40	36.00	39.55

APPLICATIONS

- Mining and processing
- Railways and transportation
- Energy
- Military
- Industrial

FEATURES




- Extremely reliable
- Constant prevailing torque
- No galling
- Locking slots independent of bolt tension



J. LANFRANCO
LOCKNUTS FOR CRITICAL BOLTED JOINTS

Disclaimer: while every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees disclaim all liability in respect to anything or the consequences of anything done or omitted regarding the whole or any part of this document.

304



You can download this
Test Certificate and/or
Report from our website:
hobson.com.au

Bolt Tension | Anti-Vibration | Product Reliability | Traceability

hobson.com.au QUALITY FASTENERS SINCE 1935

