

DID YOU KNOW?

about our...



**NEW
PRODUCT**

Flat Sling 2 Ply Protected Eye

FLAT SLING 2 PLY PROTECTED EYE POLYESTER / AS 1353

Part	Qfind	Sling Colour	Strap Width W (mm)	Strap Length L (m)	Working Load Limit WLL (kg)
ULSLPSFE010010	FS11	Purple	50	1.0	1000
ULSLPSFE010015	FS11.5	Purple	50	1.5	1000
ULSLPSFE010020	FS12	Purple	50	2.0	1000
ULSLPSFE010025	FS12.5	Purple	50	2.5	1000
ULSLPSFE010030	FS13	Purple	50	3.0	1000
ULSLPSFE010040	FS14	Purple	50	4.0	1000
ULSLPSFE010050	FS15	Purple	50	5.0	1000
ULSLPSFE020010	FS21	Green	60	1.0	2000
ULSLPSFE020020	FS22	Green	60	2.0	2000
ULSLPSFE020030	FS23	Green	60	3.0	2000
ULSLPSFE020040	FS24	Green	60	4.0	2000
ULSLPSFE020050	FS25	Green	60	5.0	2000
ULSLPSFE030010	FS31	Yellow	90	1.0	3000
ULSLPSFE030020	FS32	Yellow	90	2.0	3000
ULSLPSFE030030	FS33	Yellow	90	3.0	3000
ULSLPSFE030040	FS34	Yellow	90	4.0	3000
ULSLPSFE030050	FS35	Yellow	90	5.0	3000
ULSLPSFE030060	FS36	Yellow	90	6.0	3000



▲
ULSLPSFE010

▲
ULSLPSFE020

▲
ULSLPSFE030

APPLICATIONS

- Also known as webbing slings
- All purpose lifting

FEATURES

- Polyester webbing and protective eyes
- Polyester slings reduce damage on the load compared to chain
- Have an eye at each end
- Wider flat slings reduce force at any single point
- Colour coded to lifting capacity
- Complies with EN1492-1 and meets all performance requirements of AS 1353



You can download this
Test Certificate and/or
Report from our website:

hobson.com.au

Disclaimer: while every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees disclaim all liability in respect to anything or the consequences of anything done or omitted regarding the whole or any part of this document.

Bolt Tension | Anti-Vibration | Product Reliability | Traceability

hobson.com.au QUALITY FASTENERS SINCE 1935



231107DYK