DID YOU KNOW?

about our...

Grade 80 Master Link

Master link for single or double leg sling lifts with a variety of sling materials.

CHAIN MASTER LINK POWDER COAT / HEC / GRADE 80

Part	Qfind	Chain Size		WLL	BL
		1 Leg (mm)	2 Leg (mm)	(tonne)	(tonne)
ULCL08PML-08	CML78	8	7	2.7	10.8
ULCL08PML-10	CML108	10	8	3.5	14.0
ULCL08PML-13	CML1310	13	10	5.5	22.0
ULCL08PML-16	CML1613	16	13	9.4	37.6
ULCL08PML-20	CML2016	20	16	14.2	56.8
ULCL08PML-22	CML2220	22	20	22.3	89.2
ULCL08PML-26	CML2622	26	22	33.5	134.0
ULCL08PML-32	CML3226	32	26	40.8	163.2
ULCL08PML-36	CML3632	36	32	56.9	227.6

APPLICATIONS

- Use with Grade 80 lifting components
- Lifting with G80 1 or 2 leg chain slings,
- wire rope and synthetic slings

FEATURES

- Individually proof tested at 2.5 WLL
- 100% magnaflux crack detection
- Conforms to AS 3776









MARKINGS:

- CE (European Conformity)
- WLL (Working Load Limit)
- Trace Code (linked to certificate online)
- Manufacturer's mark



Disclaimer: while every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees disclaim all liability in respect to anything or the consequences of anything done or omitted regarding the whole or any part of this document.



hobson.com.au QUALITY FASTENERS SINCE 1935

Bolt Tension | Anti-Vibration | Product Reliability | Traceability

240125DYK