

DID YOU KNOW?

about our...



**NEW
PRODUCT**

Grade 100 Connecting Link

Connecting links easily connect lifting components to chains and eyes.

CHAIN CONNECTING LINK POWDER COAT / HEC 3776 / GRADE 100

Part	Qfind	Size	WLL	BL
		(mm)	(tonne)	(tonne)
ULCL10PCL-06	C10CL6	6	1.4	5.6
ULCL10PCL-08	C10CL8	8	2.5	10.0
ULCL10PCL-10	C10CL10	10	4.0	16.0
ULCL10PCL-13	C10CL13	13	6.7	26.8
ULCL10PCL-16	C10CL16	16	10.0	40.0
ULCL10PCL-20	C10CL20	20	16.0	64.0

APPLICATIONS

- Use with Grade 100 lifting components
- Connecting lifting components to chains and other fittings

FEATURES

- Conforms to AS 3776
- Fatigue tested at 1.5 WLL for 20,000 cycles
- 100% magnaflux crack detection



MARKINGS:

- **CE** (European Conformity)
- **WLL** (Working Load Limit)
- **Trace Code** (linked to certificate online)
- **Manufacturer's mark**



You can download this
Test Certificate and/or
Report from our website:

hobson.com.au

Disclaimer: while every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees disclaim all liability in respect to anything or the consequences of anything done or omitted regarding the whole or any part of this document.

Bolt Tension | Anti-Vibration | Product Reliability | Traceability

hobson.com.au QUALITY FASTENERS SINCE 1935



240131DYK