DID YOU KNOW?

about our...





Grade 100 Eye Safety Hook

Eye safety hook locks when a load is applied to prevent the release of chains and lifting slings.

SAFETY HOOK WITH EYE POWDER COAT / HEC 3776 / GRADE 100

Part	Qfind	Size	WLL	BL
		(mm)	(tonne)	(tonne)
ULHK10PSE-06	H10SE6	6	1.4	5.6
ULHK10PSE-08	H10SE8	8	2.5	10.0
ULHK10PSE-10	H10SE10	10	4.0	16.0
ULHK10PSE-13	H10SE13	13	6.7	26.8
ULHK10PSE-16	H10SE16	16	10.0	40.0
ULHK10PSE-20	H10SE20	20	16.0	64.0

APPLICATIONS

- Use with Grade 100 lifting components
- Lifting with chains and synthetic slings

FEATURES

- Conforms to AS 3776
- 100% magnaflux crack detection
- Safety hook prevents components from releasing if line becomes slack
- Back lever releases hook





MARKINGS:

- CE (European Conformity)
- WLL (Working Load Limit)
- Trace Code (linked to certificate online)
- Manufacturer's mark



Disclaimer: while every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees disclaim all liability in respect to anything or the consequences of anything done or omitted regarding the whole or any part of this document.

