DID YOU KNOW?

about our...



PRODUCT

XBolt® PRO Vertical Hanger

XBOLT® PRO VERTICAL HANGER ZINC PLATED (RoHS COMPLIANT) / ETA OPT 1 / C1 C2 FR / AS 5216

Part	Qfind	Diameter	Thread Length		Embedment Length	Head Height	Drive Size
		D	T1 (mm)	T2 (mm)	L (mm)	H (mm)	AF (mm)
EVXMSZ18M120060	EVX104	M10/M12	12	12	60	30	15



Opt 1





Cracked

concrete





APPLICATIONS

- · Mechanical and electrical applications
- · Pipe and ceiling hangers
- HVAC
- · Fire sprinklers
- · Cable trays
- · Suspension of mechanical services
- · Suitable for cracked and non-cracked concrete

FEATURES

- · Suitable for light- to medium-duty loads
- Suitable for small anchor spacing and edge distance applications
- · Quick and easy to install
- · Fully removable
- Dual-thread nut M10 and M12
- ETA approval Option 1
- Fire rated
- Seismic certified (C1 & C2)





Non-cracked

concrete









Disclaimer: while every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees disclaim all liability in respect to anything or the consequences of anything done or omitted regarding the whole or any part of this document. HEC product marking is the manufacturing mark of Hobson Engineering. HEC is a registered trademark of Hobson Engineering.

ENGINEERING