## **DID YOU KNOW?**

about our...





# **ERM Dual Slot Self-Lock Nut** with Free-Spinning Washer

### **ERM DUAL SLOT SELF-LOCK NUT** WITH FREE-SPINNING WASHER 316 STAINLESS / A4-80 / LANFRANCO

M16

Part	Qfind	Nominal Size	Washer Diameter	Washer Thickness	Overall Height	Nut Height	Across Flats	Across Corners
		D¹ (mm)	D <sup>2</sup> (mm)	T (mm)	H (mm)	M (mm)	S (mm)	E (mm)
NJ16NERMM08	ERM080125ZH	M8	22	1.25	11.8	4.9	13	14.38
NJ16NERMM10	ERM100150ZH	M10	22	1.50	14.8	6.3	16	17.77
NJ16NERMM12	ERM120175ZH	M12	27	1.75	16.5	7.4	18	20.03

40

2 00

22 1

97



### **FEATURES**

- Extremely reliable
- · Consistent prevailing torque


NJ16NFRMM16 FRM1602007H

- · No galling
- · Locking slots are independent of bolt tension
- · All metal is reusable
- · Dual-slotted self-locking hexagon
- Captive free-spinning disc spring maintains tension in joint under dynamic loads

#### **APPLICATIONS**

- · Mining and processing
- · Railway and transportation
- Energy
- Military
- Industrial





24

26.75



Disclaimer: while every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees disclaim all liability in respect to anything or the consequences of anything done or omitted regarding the whole or any part of this document. HEC product marking is the manufacturing mark of Hobson Engineering. HEC is a registered trademark of Hobson Engineering.

