DID YOU KNOW?

about our...





Flat Round Sampson™ Washer

FLAT ROUND SAMPSON™ WASHER ZINC PLATED (RoHS Compliant) / HEC F436M / 38-45 HRC

| Part | Diameter | Outer Diameter | Inner Diameter | Thickness |
|----------|----------|-------------------|-------------------|-----------|
| | | OD (mm) | ID (mm) | T (mm) |
| WR43ZM05 | M5 | 10.0 | 5.7 | 1.0 |
| WR43ZM06 | M6 | 13.0 | 6.9 | 1.7 |
| WR43ZM08 | M8 | 18.8 | 9.0 | 2.1 |
| WR43ZM10 | M10 | 20.0 | 11.1 | 2.1 |
| WR43ZM12 | M12 | 27.0 | 14.2 | 3.9 |
| WR43ZM14 | M14 | 30.0 | 16.2 | 3.9 |
| WR43ZM16 | M16 | 34.0 | 18.2 | 3.9 |
| WR43ZM18 | M18 | 38.0 | 20.3 | 3.9 |
| WR43ZM20 | M20 | 42.0 | 22.3 | 3.9 |
| WR43ZM24 | M24 | 50.0 | 26.3 | 4.0 |
| WR43ZM30 | M30 | 60.0 | 33.3 | 4.0 |
| WR43ZM36 | M36 | 72.0 | 39.3 | 4.0 |


APPLICATIONS

- General purpose mechanical and structural use with bolts, nuts, studs and other internally and externally threaded fasteners
- Suitable for use with ASTM A354 and ASTM F3125 fasteners
- Suitable for use with high-strength metric fasteners up to Class 10.9
- Hardened washer suitable for use with bolts and set screws up to property Class 10.9

FEATURES

 Zinc plating for corrosion protection and compatability with zinc coated fastener







Disclaimer: while every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees disclaim all liability in respect to anything or the consequences of anything done or omitted regarding the whole or any part of this document. HEC product marking is the manufacturing mark of Hobson Engineering. HEC is a registered trademark of Hobson Engineering.

