DID YOU KNOW?

about our...

Zinc Plated Allthread Rod

ALLTHREAD ROD ZINC PLATED (RoHS COMPLIANT) / DIN976 / CLASS 4.6 UTS

Part	Size	Length
		(m)
ASMSZCM03	M3	1.0
ASMSZCM04	M4	1.0
ASMSZCM05	M5	1.0
ASMSZCM06	M6	1.0-3.0
ASMSZCM08~	M8	1.0-3.0
ASMSZCM10~	M10	1.0-3.0
ASMSZCM12~	M12	1.0-3.0
ASMSZCM16~	M16	0.6-3.0
ASMSZCM20~	M20	0.6-3.0
ASMSZCM24~	M24	0.5-3.0
ASMSZCM240500	M24	0.5
ASMSZCM30~	M30	1.0-3.0
ASMSZCM36~	M36	1.0-3.0
ASMSZCM42	M42	1.0
ASMSZCM48	M48	1.0



APPLICATIONS

- Anchor bolts
- Construction
- Plumbing and contracting
- HVAC and fire sprinklers
- Suspended ceilings
- Electrical cable trays
- Stake for tomato plants

FEATURES

- True pitch and flank angle means correct minor/root diameter and correct strength
- Hobson precision allthread

Disclaimer: while every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees disclaim all liability in respect to anything or the consequences of anything done or omitted regarding the whole or any part of this document. HEC product marking is the manufacturing mark of Hobson Engineering. HEC is a registered trademark of Hobson Engineering.



MORE SIZES +

