

DID YOU KNOW?

about our...



**NEW
PRODUCT**

Metal Serrated Flat Framing

METAL SERRATED FLAT FRAMING E-COAT BLACK / AS3566 PHILLIPS DRIVE





Part	Qfind	Gauge	TPI	Length	Thread Length	Drill Point Length	Head Ø	Head Height	Drive Size
				L (mm)	T (mm)	DP (mm)	D (mm)	H (mm)	PH
T9PMKEP1224018	QB74	12	24	18	10	6	9.5	2	#2

APPLICATIONS

- Prefabricated steel wall frames

FEATURES

- Self-drilling tip. No pre-punched holes required
- Under-head serrations provide resistance to loosening
- E-coat reduces friction during installation and provides superior corrosion protection



DRILLX[®]

Disclaimer: while every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees disclaim all liability in respect to anything or the consequences of anything done or omitted regarding the whole or any part of this document. HEC product marking is the manufacturing mark of Hobson Engineering. HEC is a registered trademark of Hobson Engineering.

Bolt Tension | Anti-Vibration | Product Reliability | Traceability

hobson.com.au **QUALITY FASTENERS SINCE 1935**



240418DYK