

DID YOU KNOW?

about our...



**MORE
SIZES +**

Hot Dip Galvanised Allthread Rod

ALLTHREAD ROD

HOT DIP GALVANISED / DIN976 / CLASS 4.6 UTS

Part	Size	Length
		L (m)
ASMSGCM08~	M8	1.00-3.00
ASMSGCM10~	M10	1.00-3.60
ASMSGCM12~	M12	0.11-3.60
ASMSGCM16~	M16	0.19-3.60
ASMSGCM20~	M20	1.00-3.00
ASMSGCM24~	M24	0.50-3.00
ASMSGCM240500	M24	0.50
ASMSGCM27	M27	1.00
ASMSGCM30~	M30	1.00-3.00
ASMSGCM33	M33	1.00
ASMSGCM36~	M36	1.00-3.00
ASMSGCM39	M39	1.00
ASMSGCM42~	M42	1.00-3.00
ASMSGCM48~	M48	1.00-3.00
ASMSGCM56	M56	1.00
ASMSGCM64	M64	1.00



APPLICATIONS

- Cross bracing in steel structures
- Concrete anchoring
- Cyclone tie-down rods

FEATURES

- Hobson precision allthread
- True pitch and flank angle means right strength and correct minor/root diameter
- Hot dip galvanised to AS 1214 to a minimum of 40 µm and average of 50 µm for external applications

**NEW
SIZES +**

Disclaimer: while every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees disclaim all liability in respect to anything or the consequences of anything done or omitted regarding the whole or any part of this document. HEC product marking is the manufacturing mark of Hobson Engineering. HEC is a registered trademark of Hobson Engineering.

Bolt Tension | Anti-Vibration | Product Reliability | Traceability

hobson.com.au **QUALITY FASTENERS SINCE 1935**



240603DYK