

DID YOU KNOW?

about our...



**NEW
PRODUCT**

Panel Shims Concrete Half

PANEL SHIMS CONCRETE HALF

PLASTIC / AS 3850.1 / 20 TONNE WLL

Part	Colour	Thickness	Length	Width	Pack Qty
		(mm)	(mm)	(mm)	
MPAPLH010075	Brown	1	75	100	100
MPAPLH020075	Blue	2	75	100	100
MPAPLH030075	Green	3	75	100	100
MPAPLH050075	Yellow	5	75	100	100
MPAPLH100075	Black	10	75	100	40
MPAPLH150075	Grey	15	75	100	40
MPAPLH200075	White	20	75	100	30

APPLICATIONS

- Temporarily levels and aligns concrete panels in preparation for final attachment
- Space is then filled with grout, sealant or a cement mix
- Decking, cabinetry, door and window frames, and machinery weighing less than 20 tonnes

FEATURES

- AS 3850.1 stamped onto every shim
- 20 tonne WLL stamped onto every shim
- Ribbed profile prevents slippage
- Colour coded by thickness for easy selection
- High load strength



MARKINGS:

- WLL
(Working Load Limit)
- Australian Standard
- Hobson markings



You can download this
Test Certificate and/or
Report from our website:
hobson.com.au



1 mm

2 mm

3 mm

5 mm

10 mm

15 mm

20 mm

Disclaimer: while every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees disclaim all liability in respect to anything or the consequences of anything done or omitted regarding the whole or any part of this document. HEC product marking is the manufacturing mark of Hobson Engineering. HEC is a registered trademark of Hobson Engineering.

Bolt Tension | Anti-Vibration | Product Reliability | Traceability

hobson.com.au QUALITY FASTENERS SINCE 1935



240725DYK