DID YOU KNOW?





SS316 HBS-Bolt Hex

HBS-BOLT HEX — BLIND INSTALL & HOLLOW STEEL CONNECTIONS 316 STAINLESS / HEC / A4


Part	QFind	Nominal Size	Bolt Length	Hex Size	Length	Outer Diameter	Head Height	Across Flats	Thickness
			L (mm)	AF1 (mm)	SL (mm)	OD (mm)	H (mm)	AF2 (mm)	t (mm)
KBB16PHM100055	HBA41055	M10	55	16	30	17.75	6.4	24	6
KBB16PHM120060	HBA41260	M12	60	18	35	19.75	7.5	30	7
KBB16PHM160080	HBA41680	M16	80	24	42	25.75	10.0	36	8
KBB16PHM160100	HBA416100	M16	100	24	63	25.75	10.0	36	8
KBB16PHM200090	HBA42090	M20	90	30	50	32.75	12.5	46	10

APPLICATIONS


- For fixing steel to hollow steel sections
- For use with square, rectangular, and
- circular hollow sections
- High shear and tensile capacities
- Large grip range
- One-sided installation
- Steel framework, including gantries, bridges, stadiums, and transmission towers
- Stainless steel applications

FEATURES

- High anti-corrosive properties
- Excellent for coastal applications









Disclaimer: while every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees disclaim all liability in respect to anything or the consequences of anything done or omitted regarding the whole or any part of this document. HEC product marking is the manufacturing mark of Hobson Engineering. HEC is a registered trademark of Hobson Engineering.



hobson.com.au QUALITY FASTENERS SINCE 1935

Bolt Tension | Anti-Vibration | Product Reliability | Traceability