DID YOU KNOW?

about our...




PRODUCT


Zinc Plated Rivet Nut Reduced Head Round Knurl Open

RIVET NUT REDUCED HEAD ROUND KNURL OPEN ZINC PLATED (RoHS COMPLIANT) / HEC

Part	Size	Length	Grip Range		Hole Ø	Body Ø	Head Ø	Protrusion
	Ø (mm)	L (mm)	G (ı Min.	mm) Max.	D (mm)	B (mm)	A (mm)	P (mm)
NRMSZRKOM03090	МЗ	9.0	0.7	2.0	5	4.9	6	6.0
NRMSZRKOM03115	МЗ	11.5	2.0	3.5	5	4.9	6	6.0
NRMSZRKOM04110	M4	11.0	0.5	2.0	6	5.9	7	6.0
NRMSZRKOM04130	M4	13.0	2.5	4.0	6	5.9	7	6.0
NRMSZRKOM05115	M5	11.5	1.0	2.5	7	6.9	8	7.6
NRMSZRKOM05130	M5	13.0	2.5	4.0	7	6.9	8	7.6
NRMSZRKOM06140	M6	14.0	0.5	2.5	9	8.9	10	9.0
NRMSZRKOM06170	M6	17.0	2.5	5.0	9	8.9	10	9.0
NRMSZRKOM08165	M8	16.5	0.5	3.0	11	10.9	12	12.0
NRMSZRKOM08185	M8	18.5	3.0	5.0	11	10.9	12	12.0
NRMSZRKOM10195	M10	19.5	0.5	3.0	13	12.9	14	14.5
NRMSZRKOM10220	M10	22.0	3.5	6.0	13	12.9	14	14.5
NRMSZRKOM12220	M12	22.0	1.5	3.0	16	15.9	17	18.0
NRMSZRKOM12270	M12	27.0	4.0	6.0	16	15.9	17	18.0







APPLICATIONS

- Used in the automotive industry to fasten body panels, chassis components and other parts
- Used in construction to fasten steel sheets
- Ideal for load-bearing applications where material is too thin for bolting
- Useful for applications where there is no access for a traditional nut

FEATURES

- Also called countersunk head, flush head or thin sheet type
- Knurled body to grip and prevent rotation
- Low-profile head allows near-flush fit to sheet metal





Disclaimer: while every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees disclaim all liability in respect to anything or the consequences of anything done or omitted regarding the whole or any part of this document. HEC product marking is the manufacturing mark of Hobson Engineering. HEC is a registered trademark of Hobson Engineering.

ENGINEERING