

# DID YOU KNOW?

about our...



**NEW  
PRODUCT**

## S500 SDS Flanged Hex Head

### S500 SDS FLANGED HEX HEAD CLASS 4 / AS 3566



Part	QFind	Length	TPI	Thread Length	Drill Point Length	Head Height	Head ø	Drive Size
		L (mm)		TL (mm)	DP (mm)	H (mm)	D (mm)	AF (inch)
T9P54FH1224032	<b>Q480</b>	32	24	17	15.0	6	14	HEX 5/16"
T9P54FH1224038	<b>Q481</b>	38	24	23	15.0	6	14	HEX 5/16"
T9P54FH1224050	<b>Q482</b>	50	24	35	15.0	6	14	HEX 5/16"
T9P54FH1224065	<b>Q484</b>	65	24	50	15.0	6	14	HEX 5/16"
T9P54FH1224085	<b>Q487</b>	85	24	70	15.0	6	14	HEX 5/16"
T9P54FH1424038	<b>Q739</b>	38	24	21	17.5	7	14	HEX 3/8"





#### APPLICATIONS

- Metal-to-metal fixing
- Thick steel purlins and hot rolled steel
- Used in plumbing, steel fabrication and heating, ventilation, and air-conditioning (HVAC) systems

#### FEATURES

- Extended drill point and fine pitch threading (24 TPI) enable efficient self-drilling through metal up to 12 mm thick
- No pre-drilling required
- Corrosion resistance to Class 4 as per AS 3566.2



# DRILLX<sup>®</sup>

Disclaimer: while every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees disclaim all liability in respect to anything or the consequences of anything done or omitted regarding the whole or any part of this document. HEC product marking is the manufacturing mark of Hobson Engineering. HEC is a registered trademark of Hobson Engineering.

Bolt Tension | Anti-Vibration | Product Reliability | Traceability

[hobson.com.au](http://hobson.com.au) **QUALITY FASTENERS SINCE 1935**

