

# DID YOU KNOW?

about our...




**NEW  
PRODUCT**

## UNC Socket Screw Countersunk Hex

**UNC SOCKET SCREW COUNTERSUNK HEX**  
ZINC PLATED (RoHS COMPLIANT) / ANSI B18.3 / ASTM F835



Part	Diameter	TPI	Length	Thread Length	Hex Wrench
	Ø		L (mm)		
SCSOZC0370050	3/8	16	1/2	Full	7/32
SCSOZC0370075	3/8	16	3/4	Full	7/32
SCSOZC0370100	3/8	16	1	Full	7/32
SCSOZC0500075	1/2	13	3/4	Full	5/16
SCSOZC0500100	1/2	13	1	Full	5/16
SCSOZC0500125	1/2	13	1-1/4	Full	5/16
SCSOZC0500150	1/2	13	1-1/2	Full	5/16
SCSOZC0500175	1/2	13	1-3/4	Full	5/16
SCSOZC0500200	1/2	13	2	Full	5/16
SCSOZC0500225	1/2	13	2-1/4	Full	5/16
SCSOZC0500250	1/2	13	2-1/2	1-1/2	5/16
SCSOZC0500300	1/2	13	3	2	5/16



### APPLICATIONS

- Applications that necessitate high-tensile clamp loads
- When requiring a flush or smooth finish to the steel with no protrusion
- Automotive, machinery, and construction industries

### FEATURES

- 82 degree taper
- Reduced loadability
- Minimum tensile strength of 145 ksi for 3/8" and 160 ksi for 1/2" and over
- Due to head configurations, countersunk head screw tensile loads are based on 160,000 lbf/in<sup>2</sup>



You can download this  
Test Certificate and/or  
Report from our website:

**[hobson.com.au](http://hobson.com.au)**

Disclaimer: while every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees disclaim all liability in respect to anything or the consequences of anything done or omitted regarding the whole or any part of this document. HEC product marking is the manufacturing mark of Hobson Engineering. HEC is a registered trademark of Hobson Engineering.

Bolt Tension | Anti-Vibration | Product Reliability | Traceability

**[hobson.com.au](http://hobson.com.au) QUALITY FASTENERS SINCE 1935**



2412022DYK