DID YOU KNOW?

about our...





Round Sling

ROUND SLING POLYESTER / AS 4497

Part	QFind	Sling Colour	Strap Width	Strap Length										Working Load Limit
			W (mm)	1	1.5	2	2.5	3 L (m)	4	5	6	8	10	WLL (kg)
ULSLPSRE010~	RS1	Purple	51	✓	✓	✓	✓	✓	✓	✓	✓			1000
ULSLPSRE020~	RS2	Green	60	✓	✓	✓	✓	✓	✓	\checkmark	✓			2000
ULSLPSRE030~	RS3	Yellow	70	✓		✓		✓	✓	✓	✓	✓		3000
ULSLPSRE040~	RS4	Grey	75	✓		✓		✓	✓	✓	✓	✓		4000
ULSLPSRE050~	RS5	Red	80	✓		✓		✓	✓	✓	✓			5000
ULSLPSRE060~	RS6	Brown	85	✓		✓		✓	✓	✓	✓			6000
ULSLPSRE080~	RS8	Blue	95	✓		✓		✓	✓	✓	✓	✓		8000
ULSLPSRE100~	RS10	Orange	100	✓		✓		✓	✓	✓	✓	✓	✓	10000

NEW SIZES

APPLICATIONS

· All-purpose lifting

FEATURES

- Polyester webbing in a continuous loop
- Polyester slings reduce damage on the load compared to chain
- Continuous loop provides flexibility on lift position
- · Colour coded to lifting capacity
- Complies with EN 1492-2 and meets all performance requirements of AS 4497





Disclaimer: while every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees disclaim all liability in respect to anything or the consequences of anything done or omitted regarding the whole or any part of this document. HEC product marking is the manufacturing mark of Hobson Engineering. HEC is a registered trademark of Hobson Engineering.

