

DID YOU KNOW?

about our...



**NEW
PRODUCT**

Grade 100 Safety Hook with Clevis

Clevis safety hook locks when a load is applied to prevent the release of lifting slings.

SAFETY HOOK WITH CLEVIS POWDER COAT / HEC 3776 / GRADE 100

Part	QFind	Chain Size	WLL (tonne)	BLL (tonne)
ULHK10PSC-06	H10SC6	6	1.4	5.6
ULHK10PSC-08	H10SC8	8	2.5	10.0
ULHK10PSC-10	H10SC10	10	4.0	16.0
ULHK10PSC-13	H10SC13	13	6.7	26.8
ULHK10PSC-16	H10SC16	16	10.0	40.0
ULHK10PSC-20	H10SC20	20	16.0	64.0
ULHK10PSC-22	H10SC22	22	19.0	76.0
ULHK10PSC-26	H10SC26	26	26.5	106.0



MARKINGS:

- **CE** (European Conformity)
- **WLL** (Working Load Limit)
- **Trace Code** (linked to certificate online)
- **Manufacturer's mark**

APPLICATIONS

- Use with Grade 100 lifting components
- Lifting with chains or synthetic slings
- Clevis fitting for direct connection to chain

FEATURES

- 100% magnaflux crack detection
- Safety hook prevents components from releasing when being lifted
- Back lever releases hook



You can download this
Test Certificate and/or
Report from our website:

hobson.com.au

Disclaimer: while every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees disclaim all liability in respect to anything or the consequences of anything done or omitted regarding the whole or any part of this document. HEC product marking is the manufacturing mark of Hobson Engineering. HEC is a registered trademark of Hobson Engineering.

Bolt Tension | Anti-Vibration | Product Reliability | Traceability

hobson.com.au QUALITY FASTENERS SINCE 1935



250707DYK