



PRODUCT DATA

Cable Tie — Standard

Applications	
<ul style="list-style-type: none"> • Switchboards and server racks • Cable harnesses • Automotive • Appliance assembly 	

Material	 Nylon Polyamide PA66
-----------------	--

Finish	 Nylon Polyamide PA66
---------------	---



Features

- High Quality Nylon 66 — UL approved
- UL94V-2 fire resistance
- RoHS Compliant
- Operating temperature: -40°C to 85°C
- Indoor use

Dimensions

Part	Width	Tensile Strength	Length (mm)													
			(mm)	(kg)	150	160	200	250	300	370	430	450	530	830	1220	1530
PCT66NDD02	2.5	8.2			✓											
PCT66NDD03	3.6	18.0	✓		✓		✓									
PCT66NDD04	4.8	22.0		✓	✓	✓	✓	✓	✓							
PCT66NDD07	7.6	54.5			✓		✓	✓		✓	✓					
PCT66NDD09	9.0	79.3							✓		✓	✓	✓	✓	✓	✓

Note: avoid direct sunlight and UV exposure.

Disclaimer: while every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees disclaim all liability in respect to anything or the consequences of anything done or omitted regarding the whole or any part of this document. HEC product marking is the manufacturing mark of Hobson Engineering. HEC is a registered trademark of Hobson Engineering.

Bolt Tension | Anti-Vibration | Product Reliability | Traceability

hobson.com.au **QUALITY FASTENERS SINCE 1935**

