




PRODUCT DATA

Cable Tie — Standard

Applications	
<ul style="list-style-type: none"> • Solar Installs • Shade Cloth & Netting • Irrigation Systems • Trailer harnesses 	

Material	 Nylon Black UV Stable
-----------------	---

Finish	 Nylon Black UV Stable
---------------	--



Features

- High Quality Nylon 66 — UL approved
- UL94V-2 fire resistance
- RoHS Compliant
- Operating temperature: -40°C to 85°C
- UV resistant / outdoor use

Dimensions

Part	Width	Tensile Strength	Length (mm)																			
			(mm)	(kg)	100	150	160	200	250	300	370	430	450	530	580	730	815	880	1020	1220	1530	
PCT6UBDD02	2.5	8.2	✓			✓																
PCT6UBDD03	3.6	18.0		✓		✓		✓														
PCT6UBDD04	4.8	22.0			✓	✓	✓	✓	✓	✓												
PCT6UBDD07	7.6	54.5				✓		✓	✓		✓	✓										
PCT6UBDD09	9.0	79.3								✓		✓			✓				✓		✓	✓
PCT6UBDD12	12.6	114.0												✓	✓		✓	✓				

Disclaimer: while every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees disclaim all liability in respect to anything or the consequences of anything done or omitted regarding the whole or any part of this document. HEC product marking is the manufacturing mark of Hobson Engineering. HEC is a registered trademark of Hobson Engineering.

Bolt Tension | Anti-Vibration | Product Reliability | Traceability

hobson.com.au **QUALITY FASTENERS SINCE 1935**

