



# PRODUCT DATA

## Timber Type 17 Flanged Hex Head and Seal

Page 1 of 2

### Self Drilling Timber Screw (SDS) #12-11

#### Applications

- For fixing thin metal to timber
- Cladding/panels to timber battens

#### Material



C1022 Hardened

#### Finish



Class 4

## 12 Gauge Flanged Hex Head



#### Pullout Values

Plate Material	Timber Embedment	<sup>1</sup> Mean Load	<sup>2</sup> Characteristic Load	<sup>3</sup> Working Load
	(mm)	(N)	(N)	(N)
F7 Pine	35	5150	5300	2100
F27 Hardwood	35	7950	7450	3000

#### Mechanical Properties

Torsional Strength	<sup>1</sup> Mean Tensile Strength	<sup>1</sup> Mean Shear Strength	<sup>2</sup> Characteristic Tensile Strength	<sup>2</sup> Characteristic Shear Strength
(Nm)	(N)	(N)	(N)	(N)
9.4	16400	9850	15100	9050

Note: 1000N = 1kN

<sup>1</sup> Mean Load/Strength is the average ultimate strength of samples tested.<sup>2</sup> Characteristic Load/Strength: 95% of these screws are expected to have a strength greater than the loads shown.<sup>3</sup> Working Load is the governing minimum allowable load obtained by comparing relevant concrete and steel working loads. Factor of Safety (FOS=2.5 for steel, FOS=2.5 for timber and FOS=3.0 for concrete) are already included.

All values are obtained under laboratory conditions using DRILLX product. Safety factors should be considered for design purposes. Actual pullout loads may differ slightly depending on certain properties of the base material.

Disclaimer: While every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees, disclaim any and all liability to any person in respect of anything or the consequences of anything done or omitted to be done in reliance upon the whole or any part of this document.

**DX<sup>TM</sup>**  
**4**
**DRILLX<sup>®</sup>**

Bolt Tension | Anti-Vibration | Product Reliability | Traceability

**hobson.com.au** **QUALITY FASTENERS SINCE 1935**





# PRODUCT DATA


## Timber Type 17 Flanged Hex Head and Seal

Page 2 of 2

Part	QFind	Gauge	TPI	Length	Head Height	Head ø	Drive Size
				L (mm)	H (mm)	D (mm)	AF (inch)
T9PW4SH1211025	<b>Q600</b>	12	11	25	5.5	14.5	HEX 5/16"
T9PW4SH1211035	<b>Q602</b>			35			
T9PW4SH1211040	<b>Q603</b>			40			



### Installation



Recommended  
HEX 5/16 inch Drive Bit:

Part	QFind	Length
		(mm)
TXDIPNSS31045	BA18	45
TXDIPNSS31065	B090	65

### Installation Guide

1. Use a cordless screw driver set at max 1,500 RPM. Fit the HEX Drive Bit over the screw and place at the fastening position.
2. Apply consistently firm pressure to the screw driver while the screw is drilling.
3. Care should be taken not to over-tighten the screw.

\*Installation with impact drivers not recommended.

Disclaimer: While every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees, disclaim any and all liability to any person in respect of anything or the consequences of anything done or omitted to be done in reliance upon the whole or any part of this document.

Bolt Tension | Anti-Vibration | Product Reliability | Traceability

**hobson.com.au** **QUALITY FASTENERS SINCE 1935**