PRODUCT DATA





316 Stainless Secure Ring

Description

Secure rings provide permanent tamper-proof security to installed bolts and nuts. The ring is installed over the bolt head or nut and prevents the fastener from being tampered with.

Applications

- Fits over the hex of DIN 931 hex bolts and DIN 933 hex set screws to create a tamper-proof finish
- · Fits over DIN 934 hex nuts
- Put over the hex and use a mallet to knock down and deform the shape



Material




Finish




316 Stainless

Dimensions

Part	Nut Size	D	В	н	С	A
	(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
IRS16PDM06	M6	16	10.9	6.8	11	7.0
IRS16PDM08	M8	20	14.3	8.0	15	9.0
IRS16PDM10	M10	27	18.8	10.0	20	11.0
IRS16PDM12	M12	34	21.0	12.0	26	13.5
IRS16PDM16	M16	41	26.0	16.0	30	18.0





Disclaimer: while every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees disclaim all liability in respect to anything or the consequences of anything done or omitted regarding the whole or any part of this document. HEC product marking is the manufacturing mark of Hobson Engineering. HEC is a registered trademark of Hobson Engineering.



PRODUCT DATA





316 Stainless Secure Ring

Instructions









- 1. Install fastener as per manufacturer instructions.
- 2. Place the secure ring over the bolt head (or nut), ensuring the device is centred over the fixing.
- 3. Set the secure ring by hitting the top of the ring with a mallet. This will drive the secure ring onto the fixing.
- 4. Keep hitting the ring until it sits flush on the fixing.

Disclaimer: while every reasonable effort has been made to ensure that this document is correct at the time of printing, Hobson Engineering®, its agencies and employees disclaim all liability in respect to anything or the consequences of anything done or omitted regarding the whole or any part of this document. HEC product marking is the manufacturing mark of Hobson Engineering. HEC is a registered trademark of Hobson Engineering.

